
## GRASS TIOMOS HINGE FOR MIRROR & GLASS

- For glass thickness 3-8 mm
- Opening angle 125°
- . 3-dimensional adjustment with appropriate mounting plate
- Fastening through door-side gluing of a zinc alloy adapter
- Connection of the hinge to the adapter using a cam
- High overlay up to 19 mm
- · For glas doors or double sided mirro doors
- · Diecast nickel-plated
- Adapter must be ordered separatly
- All reveals must be at least 1.5 mm, otherwise there is a risk of breakage.
- · Order qty: 1pcs


	Cat. No.
With spring	80290*
Without spring	80291




# Number of hinges 500 mm 18-22 kg □ 13-17 kg 🗀 7-12 kg




Overlay




Half overlay





#### 90° Opening Angle Restraint






- Opening Angle Restraint, 900
- Prevents the door from butting against front panels or walls with corner
- For use with Tiomos M9, M0 and Mirro 125o hinges
- Black plastic
- Order qty: 1pcs

Code:

81995

#### Grass Tiomos Adapter



- · Grlued into position, no need to route or drill the door
- Stainless steel
- Order qty: 1pcs

Z = 0	verlay e + 7 mm
with n	iounting plate (f), height 0 mm
Z×O	verlay e + 9 mm
with n	ounting plate (f), height 2 mm

For Morror	80292
For Glass	80293

### Power Adhesive




- Power Adhesive, 12 ml, for Almost any Material Combinations, MultiFix
- 1hr curing time, 3-5 minutes handling strength
- · Low odour
- Weather resistant
- 12 ml cartridge
- · Order qty: 1pcs

21-	
Code:	90610

#### Grass Tiomos inline mounting plate





- · For TIOMOS click on fixing hinges only
- · Varianta screw fixing. Order fixing screw separately
- Two part plate with + 2 mm height adjustment via worm screw
- Nickel-plated steel
- Order qty: 1pcs





0 mm	81976
2 mm	81977