TIOMOS 160

160° wide-angle hinge (door thicknesses up to 32 mm)



- 160° opening angle
- Convenient depth adjustment via worm gear
- For cabinets with inset drawers or pull-out shelves
- Optimum reveals for door thicknesses up to 32 mm
- 3-dimensional adjustment with appropriate mounting plate
- Minimum reveals
- · Shallow cup depth

Available in 3 versions:

- With integrated damper (3 adjustable damping levels)
- Without integrated damper
- Without self-closing mechanism (without spring)

ORDER INFORMATION FOR DRILLING PATTERN 45/9.5

Door overlay		Cranking	Damper			Artno.		
			with	without	without spring	Click-on For screw fixing	Click-on For press fitting	Impresso without tools
Full overlay ¹		0	-	-	-	F028138561	F028 138 564	F017 139 350
			-		-	F045138499	F045138502	F034139321
			-			F046138621	-	F035139378
Overlay ¹		3		-	-	F028138562	F028138565	F017139351
			-		-	F045138500	F045138503	F034139322
			-			F046138622	-	F035 139 379
		9.5	-	-	-	F028138563	F028138566	F017139352
Half overlay ¹			-		-	F045138501	F045138504	F034 139 323
			-			F046138623	-	F035 139 380


 $^{^{\}mbox{\tiny 1}}$ Cup material: Zamak, nickel-plated / Arm material: Zamak, nickel-plated

ACCESSORIES

	Designation	Artno.	
	120° opening angle reduction clip	F072 135 753	
A00	Tipmatic Pin for wooden and aluminium frame doors	F069 135 396	

	Designation	Artno.
Boggs.	Countersunk wood screw Ø 3.5 x 15 mm	F146 073 976
	Unclipping protector	F072 135 807

MITRED APPLICATION (ON ALL SIDES)




With 0 cranking, mounting plate height 19 mm and cup distance 4 mm, door and cabinet edges can meet at mitred angles on all 4 sides.

Use 120° opening angle reduction clip.

		Mitred application circumferential	Mitred application lateral
		R (min.)	R (min.)
(TS)	19-20	1.0	0
SSS	22	2.0	0
ķ	24	3.0	1.0
thickness	26	4.2	2.5
	28	5.4	3.8
Door	30	6.5	5.3

ZERO PROTRUSION



For cabinets with inset drawers.

At 0 cranking, and with all mounting plate thicknesses, the door protrudes inwards at 90°. With cranking size 3 and mounting plate height 3 mm, the door will be flush with the cabinet.

Tiomos mounting plates	102
Accessories	112

Tipmatic	302
Technical information	116

Assembly aids	354