

TRITECH CE Ref. 1750 CE

Suitable for heavy weight flush doors tested to BS EN 1935 Grade 14-160kgs

TRITECH

Technical details

| | |
|--------------------|----------|
| load capacity | 160.0 kg |
| overall length | 100.0 mm |
| overall width | 75.0 mm |
| knuckle diameter | 13.0 mm |
| material thickness | 3.5 mm |
| screws | 10.0 g |

Note

High performance concealed bearing brass hinge with 25 year performance guarantee.
Maintenance free.

CE marked versions suitable for use on 1 hour and 1/2 hour fire and escape doorsets - supplied complete with intumescent pads.
Security dog bolt, radius corner and designer finial options available.
Supplied complete with fixing screws if required. Special finishes available upon request.

Product features

- solid brass high performance concealed bearing hinge
- suitable for heavy weight flush doors tested to BS EN 1935 Grade 14
- CE marked 30 & 60 min. fire rated options
- maintenance free, 25 year performance guarantee
- security bolt and radius corner options available

Classification key

| | | | | | | | |
|---|---|---|---|---|---|---|----|
| 4 | 7 | 7 | 1 | 1 | 4 | 0 | 14 |
|---|---|---|---|---|---|---|----|

Quality marks



Items (DIN reference: DIN right and left hand)

| | |
|--------------|----------|
| Finish(es) | ohne |
| packing unit | à 5 Pair |
| item number | 1750 CE |

